

View Online at https://aerobasegroup.com/nsn/5910-00-904-9741

## **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

## Body Diameter:

0.100 inches

### **Body Length:**

0.270 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

# Capacitance Value Per Section:

10.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

# Criticality Code Justification:

Test

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Ceramic

### Insulation Resistance At Reference Temp:

20000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

### **Terminal Surface Treatment:**

Solder

# Test Data Document:

94756-441-0763 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-00-904-9741

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

