NSN 5910-00-905-4057

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-905-4057 **Thread Class:** Any acceptable **Body Style:** Piston **Overall Length:** 0.891 inches **Terminal Length:** 2.000 inches **Bushing Diameter:** 0.312 inches **Bushing Length:** 0.250 inches **Body Length:** 0.641 inches **Overall Diameter:** 0.250 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.625 inches Center To Center Distance Between Terminals Parallel To Diameter: Any acceptable **Terminal Diameter:** 0.025 inches **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encapsulated **Bushing Shape: Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches

Capacitance Range In Picofarads: +0.4/+2.5 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

NSN 5910-00-905-4057 Glass Dielectric Variable Capacitor - Page 2 of 2



Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0