NSN 5910-00-905-7771

Electrolytic Fixed Capacitor - Page 1 of 2



Body Style: Wio mtg lacilities, axial terminals Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.375 inches Body Length: 2.820 inches Sochematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 de single section 15.00/+15.00 percent single section 1-15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent:
Wio mig facilities, axial terminals Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.375 inches Body Length: 2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius De Leakage At Maximum Operating Temp: 25.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Reliability Indicator: Not established Termial Length: 1.500 inches Body Diameter: 0.375 inches Body Length: 2.820 inches Body Length: 2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 de single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Not established Terminal Length: 1.500 Inches Body Diameter: 0.375 Inches Body Length: 2.820 Inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 do single section Tolerance Range Per Section: 1-15.00/+15.00 percent single section Capacitude Continuous Voltage Rating And Type Per Section: 301.0 do single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material:
Terminal Length: 1.500 inches Body Diameter: 0.375 inches Body Length: 2.820 inches Body Length: 2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
1.500 inches Body Diameter: 0.375 inches Body Length: 2.820 inches Body Length: 2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius De Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 de single section 150erance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Body Diameter: 0.375 inches Body Length: 2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 15.00/+15.00 percent single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
0.375 inches Body Length: 2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.00.0 single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Body Length: 2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
2.820 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
No common or grounded electrode (s) Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 de single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Anode Type: Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Plain foil Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Impedance At Minimum Operating Tempurature In Ohms: 200.0 Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Electrical Polarization: Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Polarized Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Capacitance Value Per Section: 10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
10.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Dc Leakage At Maximum Operating Temp: 225.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
300.0 dc single section Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Tolerance Range Per Section: -15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
-15.00/+15.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Case Material: Metal Capacitive Electrode Material: Tantalum
Metal Capacitive Electrode Material: Tantalum
Capacitive Electrode Material: Tantalum
Tantalum
rower ractor at Reference reinipurature in rescent.
10.0000
Dc Leakage At Reference Temp:
45.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-00-905-7771

Electrolytic Fixed Capacitor - Page 2 of 2



	Ī	erm	inal	Type	And	Quantit	y:
--	---	-----	------	-------------	-----	---------	----

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0