## NSN 5910-00-908-0402

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-908-0402 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.289 inches **Body Length:** 0.686 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 1.2 **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 150.000 microfarads single section **Nonderated Operating Temp:** Between -80.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8000.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 6.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 8.0000 Dc Leakage At Reference Temp: 9.000 microamperes

**Terminal Surface Treatment:** 

Solder

## NSN 5910-00-908-0402 Electrolytic Fixed Capacitor - Page 2 of 2



Case insulation Material:
Plastic
Terminal Type And Quantity
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0