Paper Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-909-7850

# Body Style:

W/o mtg facilities, terminal (s) on one surface

### **Reliability Indicator:**

Not established

## **Terminal Length:**

Between 0.340 inches and 0.460 inches

### **Body Length:**

Between 3.630 inches and 3.690 inches

#### **Body Width:**

Between 1.940 inches and 2.000 inches

### **Body Height:**

Between 3.440 inches and 3.560 inches

## Center To Center Distance Between Terminals Parallel To Length:

Between 0.780 inches and 0.840 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Internal Electrical Connection Type:**

Inserted tab

### **Capacitance Value Per Section:**

15.000 microfarads single section

## Nonderated Operating Temp:

Between 5.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 ac-rms single section

#### **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

### Case Material:

Metal

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.500

#### **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 quick disconnect, male, double blade or 2 quick disconnect, male, single blade

## Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A010b0