## NSN 5910-00-910-6112

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-910-6112 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 0.312 inches **Body Diameter:** 0.875 inches **Body Length:** 0.732 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 20.0 **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 240.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 518.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 18.0 dc single section **Tolerance Range Per Section:** -15.00/+75.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum** Dc Leakage At Reference Temp: 86.500 microamperes **Terminal Type And Quantity:** 1 tab, solder lug and 1 solder stud Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5910-00-910-6112

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0