# NSN 5910-00-911-3034

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-911-3034

## **Body Style:**

W/o mtg facilities, terminal (s) on one end

## **Reliability Indicator:**

Not established

# **Terminal Length:**

0.312 inches

#### **Body Diameter:**

1.375 inches

#### **Body Length:**

4.000 inches

## Center To Center Distance Between Terminals Parallel To Diameter:

0.438 inches

#### **Terminal Diameter:**

0.141 inches

## Center To Center Distance Between Mounting Facilities Parallel To Diameter:

0.844 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

#### Anode Type:

Plain foil

# **Electrical Polarization:**

Polarized

## Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

2 threaded mounting holes

## Capacitance Value Per Section:

1800.000 microfarads single section

## Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

#### Thread Size:

0.138 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

60.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+100.00 percent single section

#### Case Material:

Metal

#### **Capacitive Electrode Material:**

Aluminum

## **Dissipation Factor At Reference Tempurature In Percent:**

0.006

Electrolytic Fixed Capacitor - Page 2 of 2



Dc Leakage At Reference Temp:

100.000 microamperes

# Terminal Type And Quantity:

2 standoff, solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0