

View Online at <https://aerobasegroup.com/nsn/5910-00-911-9272>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

1.125 inches

Body Width:

0.625 inches

Body Height:

0.375 inches

Center To Center Distance Between Terminals Parallel To Length:

0.719 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Missile, all-weather antiship, harpoon (agm-84); spruance class dd (963); forrestal class cv; sturgeon class ssn (637); interrogator set (a0681) (an/upx0270; los angeles class ssn (688); virginia class cgn (41); ticonderoga class cg (47); missile, air-to-air, phoenix (aim-54)

Insulation Resistance At Maximum Operating Temp:

1500.0 megohm-microfarads

Capacitance Value Per Section:

0.330 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

25000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polyester

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0