NSN 5910-00-912-1466

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-912-1466 |
|---|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.240 inches and 0.360 inches |
| Body Diameter: |
| Between 0.984 inches and 1.016 inches |
| Body Length: |
| Between 1.844 inches and 1.908 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Features Provided: |
| Hermetically sealed case |
| Insulation Resistance At Maximum Operating Temp: |
| 10.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 1.500 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 600.0 dc single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Metal |
| Power Factor At Reference Tempurature In Percent: |
| 1.000 |
| Terminal Surface Treatment: |
| Solder |
| Dielectric Material: |
| Plastic polyethylene terephthalate |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |

No

Fiig:

A010b0