NSN 5910-00-912-4412

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-912-4412 **Body Style:** W/mtg hol (s)/slot(s), terminals on opposite surfaces **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Body Length:** 3.562 inches **Body Width:** 1.000 inches **Body Height:** 1.875 inches **Center To Center Distance Between Terminals Parallel To Length:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: **4.220** inches **Schematic Diagram Designator:** One terminal common to each section Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.000 inches **Internal Electrical Connection Type:** Extended foil

Mounting Facility Type And Quantity:

3 unthreaded mounting holes

Section Quantity:

2

Insulation Resistance At Maximum Operating Temp:

15.0 megohm-microfarads

Capacitance Value Per Section:

0.500 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc all sections

Tolerance Range Per Section:

-10.00/+10.00 percent 2nd section

Case Material:

Metal

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

NSN 5910-00-912-4412 Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Dielectric Material:
Paper and plastic
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiia:

A010b0