NSN 5910-00-912-5093

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
Between 1.625 inches and 2.625 inches
Body Length:
Between 1.438 inches and 1.593 inches
Body Width:
Between 0.443 inches and 0.561 inches
Body Height:
Between 0.828 inches and 0.936 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.500 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 100.0 degrees celsius
Nandarated Continuous Valtage Dating And Type Day Section.
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
600.0 dc single section
600.0 dc single section Tolerance Range Per Section:
600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic
600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads
600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
600.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyethylene terephthalate
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyethylene terephthalate Terminal Type And Quantity:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyethylene terephthalate Terminal Type And Quantity: 2 uninsulated wire lead

Demilitarization: No

NSN 5910-00-912-5093

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0