NSN 5910-00-912-6846

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-912-6846

Body Style:
W/thd bushing mtg, terminals on opposite ends
Reliability Indicator:
Not established
Terminal Length:
0.296 inches
Body Diameter:
0.562 inches
Body Length:
1.125 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
5.0 megohm-microfarads
Capacitance Value Per Section:
1.500 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.312 inches
Nonderated Continuous Voltage Rating And Type Per Section:
150.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
2000.0 megohm-microfarads
Power Factor At Reference Tempurature In Percent:
1.5000
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5910-00-912-6846

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0