## NSN 5910-00-912-7879

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-912-7879  |
|--|
| Body Style:  |
| W/o mtg facilities, axial terminals  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 1.625 inches   |
| Body Diameter:   |
| 0.594 inches   |
| Body Length:   |
| 1.438 inches   |
| Terminal Diameter:   |
| 0.032 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Features Provided:   |
| Hermetically sealed case   |
| Capacitance Value Per Section:   |
| 0.220 microfarads single section   |
| Nonderated Operating Temp:   |
| Between -55.0 degrees celsius and 125.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:   |
| 600.0 dc single section  |
| Tolerance Range Per Section:   |
| -10.00/+10.00 percent single section   |
| Case Material:   |
| Metal  |
| Dissipation Factor At Reference Tempurature In Percent:  |
| 1.0000   |
| Terminal Surface Treatment:  |
| Solder   |
| Case Insulation Material:  |
| Plastic  |
| Test Data Document:  |
| 81349-mil-c-18312 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 2 uninsulated wire lead  |
| Specification Data:  |
| 81349-mil-c-18312/2b government specification  |
| Shelf Life:  |

--

N/a

**Unit Of Measure:** 

## NSN 5910-00-912-7879

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0