## NSN 5910-00-912-9268



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-912-9268 **Body Style:** W/thd bushing mtg, terminal (s) on one end **Reliability Indicator:** Not established **Body Diameter:** 1.375 inches **Body Length:** 2.750 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **Mounting Facility Screw Thread Series Designator: Mounting Facility Type And Quantity:** 1 threaded bushing **Section Quantity: Features Provided:** Mounting hardware and hermetically sealed case **Capacitance Value Per Section:** 47.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.875 inches Nonderated Continuous Voltage Rating And Type Per Section: 450.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Terminal Surface Treatment:** Nickel **Terminal Type And Quantity:** 2 tab, solder lug

N/a

Shelf Life:

## NSN 5910-00-912-9268

Electrolytic Fixed Capacitor - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A010b0