

View Online at https://aerobasegroup.com/nsn/5910-00-913-0228

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.625 inches

## Body Diameter:

0.594 inches

#### **Body Length:**

1.188 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Features Provided:

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

## **Capacitance Value Per Section:**

0.100 microfarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

## **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

## **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

25000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

#### **Terminal Surface Treatment:**

Solder

# **Test Data Document:**

81349-mil-c-19978/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-00-913-0228

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

