## NSN 5910-00-913-7471

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-913-7471

D ~	برام	Stv	۱۸.
DU	uv	SIV	ıe:

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not establishednot established

**Body Diameter:** 

0.225 inches

**Body Length:** 

0.687 inches

**Terminal Height From Body:** 

1.312 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

1000.0 megohms

**Capacitance Value Per Section:** 

30.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

**Tolerance Range Per Section:** 

-1.00/+1.00 percent single section

Case Material:

Ceramic

**Insulation Resistance At Reference Temp:** 

50000.0 megohms

**Quality Factor At Reference Temp:** 

1000.0000

**Terminal Surface Treatment:** 

Solder

Test Data Document:

81349-mil-c-20+6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-00-913-7471

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0