NSN 5910-00-914-1228

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-914-1228 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** Between 0.147 inches and 0.282 inches **Body Length:** 0.800 inches **Body Width:** 0.700 inches **Body Height:** 0.340 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.400 inches **Terminal Diameter:** Between 0.031 inches and 0.037 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Capacitance Value Per Section:** 0.100 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 50000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.5000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyester **Terminal Type And Quantity:** 2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-00-914-1228

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0