

View Online at <https://aerobasegroup.com/nsn/5910-00-916-0798>

Thread Class:

2a

Body Style:

Piston

Terminal Length:

2.000 inches

Bushing Diameter:

0.250 inches

Bushing Length:

0.250 inches

Body Length:

0.656 inches

Overall Diameter:

0.312 inches

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-60.0/+10.0 single section

Terminal Diameter:

0.016 inches

Quality Factor At 25 Deg Celsius:

500.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 5.000 inch-ounces

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Bushing Width:

0.225 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Capacitance Range In Picofarads:

+0.6/+9.0 single section

Nonderated Voltage Rating And Type:

1250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Material:

Glass inclosure

Precious Material And Location:

Internal and external surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0