

View Online at <https://aerobasegroup.com/nsn/5910-00-917-0666>

Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

1.620 inches 1.620 inches 1.620 inches

Body Diameter:

0.170 inches

Body Length:

0.320 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Helicopter, uscg search and rescue, hh-60j; radar, series an/sps-4 (v); helicopter, search and rescue, hh-60h; helicopter, carrier based asw, sh-60f; ticonderoga class cg (47); sturgeon class ssn (637); virginia class cgn (41); los angeles class ssn (688); landing craft air cushion (lcac)

Capacitance Value Per Section:

0.220 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

50000.0 megohms

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0