NSN 5910-00-920-3858

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-920-3858

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.680 inches
Body Width:
0.200 inches
Body Height:
0.270 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.220 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 100.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Case Material: Plastic
Plastic
Plastic Insulation Resistance At Reference Temp:
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment:
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Plastic Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: