

View Online at <https://aerobasegroup.com/nsn/5910-00-921-6459>

Body Style:

W/thd bushing mtg, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.832 inches

Body Diameter:

0.656 inches

Body Length:

1.781 inches

Schematic Diagram Designator:

Feedthrough

Anode Type:

Solid

Impedance At Minimum Operating Temperature In Ohms:

500.0

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

4.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.375 inches

Dc Leakage At Maximum Operating Temp:

120.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

360.0 dc single section

Tolerance Range Per Section:

-15.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Temperature In Percent:

6.100

Equivalent Series Resistance At Reference Temperature In Ohms:

20.00

Dc Leakage At Reference Temp:

12.000 microamperes

Terminal Type And Quantity:

1 solder stud and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0