

View Online at https://aerobasegroup.com/nsn/5910-00-924-9541

## **Body Style:**

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

# **Reliability Indicator:**

Not establishednot establishednot established

#### **Terminal Length:**

1.500 inches 1.500 inches

#### **Body Diameter:**

0.265 inches

#### **Body Length:**

0.156 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.215 inches and 0.285 inches

#### **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

10000.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-56.0/+22.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+80.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

10.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

5.0000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-924-9541

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

