NSN 5910-00-925-3776

A010b0

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-925-3776

| Body Style: |
|---|
| W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.250 inches |
| Body Diameter: |
| 0.290 inches |
| Body Length: |
| 0.540 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 27.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 500.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -60.0/+60.0 single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 13499-929-1574 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |