

View Online at <https://aerobasegroup.com/nsn/5910-00-925-6531>

Body Style:

W/twist tab mtg, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.296 inches

Body Diameter:

1.503 inches

Body Length:

4.562 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Spruance class dd (963), nimitz class cvn, kidd class ddg, wasp class lhd, oliver perry class ffg, tarawa class lha, forrestal class cv, virginia class cgn (41), sturgeon class ssn (637)

Capacitance Value Per Section:

5000.000 microfarads single section

Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-10.00/+85.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0