NSN 5910-00-926-2314

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-926-2314

Body Style:						
W/o mtg facilities, axial terminals						
Reliability Indicator:						
Not established						
Terminal Length:						
1.500 inches						
Body Diameter:						
0.185 inches						
Body Length:						
0.610 inches						
Schematic Diagram Designator:						
Electrod (s) grounded to case, w/gnd terminal						
Electrical Polarization:						
Polarized						
Features Provided:						
Hermetically sealed case						
Capacitance Value Per Section:						
4.700 microfarads single section						
Nonderated Operating Temp:						
Between -55.0 degrees celsius and 85.0 degrees celsius						
Dc Leakage At Maximum Operating Temp:						
35.0 milliamperes						
Nonderated Continuous Voltage Rating And Type Per Section:						
50.0 dc single section						
Tolerance Range Per Section:						
-20.00/+20.00 percent single section						
Case Material:						
Metal						
Capacitive Electrode Material:						
Tantalum						
Dissipation Factor At Reference Tempurature In Percent:						
3.0000						
Dc Leakage At Reference Temp:						
3.500 microamperes						
Terminal Surface Treatment:						
Solder						
Test Data Document:						
81349-mil-c-26655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification						
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain						
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).						
Terminal Type And Quantity:						
2 uninsulated wire lead						

N/a

Shelf Life:

NSN 5910-00-926-2314

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0