NSN 5910-00-926-9824

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-926-9824

view Online at https://aerobasegroup.com/hsn/5910-00-926-9824
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Terminal Length:
1.500 inches
Body Diameter:
0.185 inches
Body Length:
0.474 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
6.3 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
75.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
2.0000
Dc Leakage At Reference Temp:
0.500 microamperes
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-39003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-926-9824

Electrolytic Fixed Capacitor - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0