NSN 5910-00-927-0775

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-927-0775 |
|---|
| Body Style: |
| W/o mtg facilities, terminal (s) on one end |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 1.500 inches |
| Body Length: |
| 4.061 inches |
| Schematic Diagram Designator: |
| One terminal common to each section |
| Anode Type: |
| Plain foil |
| Impedance At Minimum Operating Tempurature In Ohms: |
| 170.0 |
| Electrical Polarization: |
| Polarized |
| Section Quantity: |
| 2 |
| Capacitance Value Per Section: |
| 47.000 microfarads all sections |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc all sections |
| Tolerance Range Per Section: |
| -10.00/+50.00 percent 2nd section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 12.0000 |
| Dc Leakage At Reference Temp: |
| 200.000 microamperes |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |

Terminal Type And Quantity:

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

3 standard tube base

Shelf Life:

N/a

NSN 5910-00-927-0775

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0