## NSN 5910-00-927-2730

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-927-2730

Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.750 inches
Body Length:
2.000 inches
Body Width:
2.000 inches
Body Height:
1.125 inches
Center To Center Distance Between Terminals Parallel To Length:
1.063 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.375 inches
Schematic Diagram Designator:
Delta connected
Mounting Facility Type And Quantity:
2 unthreaded mounting holes
Section Quantity:
3
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
0.020 microfarads all sections
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
90.0 ac-rms all sections
Tolerance Range Per Section:
-10.00/+10.00 percent all sections
Case Material:
Metal

1.000

**Terminal Surface Treatment:** 

50000.0 megohm-microfarads

**Insulation Resistance At Reference Temp:** 

**Dissipation Factor At Reference Tempurature In Percent:** 

Solder

## NSN 5910-00-927-2730

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Dielectric Material:
Plastic polycarbonate
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0