## NSN 5910-00-928-1130

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-928-1130 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 0.600 inches **Body Width:** 0.375 inches **Body Height:** 0.195 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.190 inches and 0.210 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 8.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 15.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: Terminal Surface Treatment:** Solder **Test Data Document:** 97983-131188 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-00-928-1130

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0