## NSN 5910-00-928-1176

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-928-1176 |
|---|
| Body Style:   |
| W/o mtg facilities, axial terminals                           |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 1.500 inches  |
| Body Diameter:  |
| 0.296 inches  |
| Body Length:  |
| 1.031 inches  |
| Schematic Diagram Designator:                                 |
| No common or grounded electrode (s)                           |
| Anode Type:   |
| Etched foil   |
| Impedance At Minimum Operating Tempurature In Ohms:           |
| 830.0   |
| Electrical Polarization:                                      |
| Nonpolarized  |
| Capacitance Value Per Section:                                |
| 4.000 microfarads single section                              |
| Nonderated Operating Temp:                                    |
| Between -55.0 degrees celsius and 125.0 degrees celsius       |
| Dc Leakage At Maximum Operating Temp:                         |
| 30.0 milliamperes   |
| Nonderated Continuous Voltage Rating And Type Per Section:    |
| 65.0 dc single section  |
| Tolerance Range Per Section:                                  |
| -15.00/+50.00 percent single section                          |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:                                |
| Tantalum  |
| Dc Leakage At Reference Temp:                                 |
| 3.000 microamperes  |
| Terminal Surface Treatment:                                   |
| Solder  |
| Case Insulation Material:                                     |
| Plastic   |
| Terminal Type And Quantity:                                   |
| 2 uninsulated wire lead                                       |
| Shelf Life:   |

N/a

## NSN 5910-00-928-1176

Electrolytic Fixed Capacitor - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A010b0