## NSN 5910-00-928-3150

Paper Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-928-3150

Body Style:  Wo mtg facilities, terminals on opposite surfaces  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Length:  0.530 inches  Body Width:  0.301 inches  Body Width:  0.180 inches  Body Height:  0.180 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.10 om incrolarast single section  Nonderated Operating Temp:  Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  20.00 do single section  Tolerance Range Per Section:  -20.00 to 20.00 percent single section  Case Material:  Pleasic  Test Data Document:  81349-mill-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Sheff Life:  No  Unit of Measure:	
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 0.530 inches Body Width: 0.330 inches Body Width: 0.310 inches Body Height: 0.180 inches Body Height: 0.180 inches Body Height: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.100 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0.0 do single section Tolerance Range Per Section: -20.00 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-mill-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:	Body Style:
Not established Terminal Length: 1.500 inches Body Length: 0.530 inches Body Width: 0.301 inches Body Width: 0.310 inches Body Height: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.100 microtarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 do single section Tolerance Range Per Section: -20.00 to 20.0 percent single section Case Material: Plastic Test Data Document: B13439-mile-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shoft Life: N/a Unit Of Measure: Demilitarization: No Filig:	W/o mtg facilities, terminals on opposite surfaces
Terminal Length:  1.500 inches Body Length:  0.530 inches Body Width:  0.310 inches Body Height:  0.180 inches Body Height:  0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section:  0.100 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:  200.0 do single section Tolerance Range Per Section:  -20.00 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
1.500 inches  Body Length: 0.530 inches Body Width: 0.310 inches Body Width: 0.180 inches Body Height: 0.180 inches  Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.100 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 de single section Tolerance Range Per Section: -20.00 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-milk-c70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Not established
Body Length: 0.530 inches Body Width: 0.310 inches Body Height: 0.180 inches Body Height: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.100 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -20.00 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-mil-c-70327 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Terminal Length:
0.330 inches  Body Width: 0.310 inches  Body Height: 0.310 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 0.100 microfarads single section  Nonderated Operating Temp:  Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 20.0.0 do single section  Tolerance Range Per Section: -20.00 to 20.00 percent single section  Case Material: Plastic  Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Flig:	1.500 inches
Body Width:  0.310 inches Body Height: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.100 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0.0 do single section Tolerance Range Per Section: -20.0.0 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-mill-o-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Body Height: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.100 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	0.530 inches
Body Height: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.100 microfarads single section Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	Body Width:
O. 180 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section: 0.100 microfarads single section  Nonderated Operating Temp:  Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document:  81349-mill-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	0.310 inches
Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section: 0.100 microfarads single section  Nonderated Operating Temp:  Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	Body Height:
No common or grounded electrode (s)  Capacitance Value Per Section: 0.100 microfarads single section  Nonderated Operating Temp:  Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	0.180 inches
Capacitance Value Per Section:  0.100 microfarads single section  Nonderated Operating Temp:  Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section:  -20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Schematic Diagram Designator:
0.100 microfarads single section  Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -20.00 to 20.00 percent single section  Case Material: Plastic  Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	No common or grounded electrode (s)
Nonderated Operating Temp: Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00 to 20.00 percent single section Case Material: Plastic Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Capacitance Value Per Section:
Between -65.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section:  -20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	0.100 microfarads single section
Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section:  -20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Nonderated Operating Temp:
200.0 dc single section  Tolerance Range Per Section: -20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Between -65.0 degrees celsius and 85.0 degrees celsius
Tolerance Range Per Section: -20.00 to 20.00 percent single section  Case Material: Plastic  Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Nonderated Continuous Voltage Rating And Type Per Section:
-20.00 to 20.00 percent single section  Case Material:  Plastic  Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fitig:	200.0 dc single section
Case Material: Plastic  Test Data Document: 81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Tolerance Range Per Section:
Plastic  Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	-20.00 to 20.00 percent single section
Test Data Document:  81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Case Material:
81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Plastic
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	81349-mil-c-70327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
2 uninsulated wire lead  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 uninsulated wire lead
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A010b0	Fiig:
	A010b0