

View Online at <https://aerobasegroup.com/nsn/5910-00-929-2607>

Body Style:

W/o mtg facilities terminal (s) on one surface/w/o mtg facilities terminal(s) on one surface/w/o mtg facilities terminal(s) on one surface

Mil-std-1276 Wire Lead Type Designator:

Ddd

Reliability Indicator:

Not established/not established/not established

Terminal Length:

1.500 inches 1.500 inches 1.500 inches

Body Length:

Between 0.285 inches and 0.300 inches

Body Width:

Between 0.285 inches and 0.300 inches

Body Height:

Between 0.090 inches and 0.100 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.190 inches and 0.210 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

47000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-20.0/+10.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

10600.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.5000

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0