NSN 5910-00-930-4557

Gas Dielectric Variable Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-930-4557 |
|---|
| Thread Class: |
| 2b |
| Body Style: |
| Concentric |
| Terminal Length: |
| 0.380 inches |
| Overall Height: |
| Between 3.655 inches and 3.775 inches |
| Alternating Current Rating In Amps: |
| 35.0 |
| Body Height: |
| Between 3.280 inches and 3.400 inches |
| Overall Diameter: |
| 2.120 inches |
| Fragility Factor: |
| Moderately rugged |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Adjustment Device Torque: |
| 22.000 inch-ounces |
| Mounting Facility Type And Quantity: |
| 6 threaded hole |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 175.0 degrees celsius |
| Thread Size: |
| 0.138 inches |
| Capacitance Range In Picofarads: |
| +8.0/+200.0 single section |
| Nonderated Voltage Rating And Type: |
| 5000.0 ac rms single section |
| Adjustment Device Drive Type And Quantity: |
| 1 knob |
| Material: |
| Glass base |
| Terminal Type And Quantity: |
| 2 ferrule |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5910-00-930-4557

Gas Dielectric Variable Capacitor - Page 2 of 2



Fiig:

A096a0