NSN 5910-00-930-7918



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2	HOTO
View Online at https://aerobasegroup.com/nsn/5910-00-930-7918	
Body Style:	
W/mtg tabs/flanges, terminal (s) on one surface	
Reliability Indicator:	
Not established	
Terminal Length:	
0.750 inches	
Body Length:	
2.000 inches	

Body Width: 2.000 inches

Body Height:

1.500 inches

Center To Center Distance Between Terminals Parallel To Length:

1.062 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

40.0 megohm-microfarads

Capacitance Value Per Section:

4.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Power Factor At Reference Tempurature In Percent:

1.0000

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-00-930-7918

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0