NSN 5910-00-931-7067

Not establishednot established

1.500 inches 1.500 inches 1.500 inches

Body Style:

Reliability Indicator:

Terminal Length:

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-931-7067

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

| Body Diameter: |
|---|
| 0.275 inches |
| Body Length: |
| 0.156 inches |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.250 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.022 microfarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -22.0/+22.0 without voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 25.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 10000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 5.0000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |

NSN 5910-00-931-7067

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0