NSN 5910-00-932-2774

Body Style:

Overall Length: 1.312 inches

Terminal Length:

Between 1.125 inches and 1.249 inches

0.703 inches **Body Length:**

4 wire lead

Piston

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-932-2774

Overall Diameter: 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** Between 0.172 inches and 0.296 inches **Terminal Diameter:** 0.030 inches **Center To Center Distance Between Mounting Facilities Parallel To Diameter:** Between 0.172 inches and 0.296 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.078 inches and 1.202 inches **Quality Factor At 25 Deg Celsius:** 350.0 **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Mounting Facility Type And Quantity:** 4 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0/+52.0 single section **Nonderated Voltage Rating And Type:** 1000.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Capacitance Drift In Picofarads:** 0.08 single section **Terminal Type And Quantity:**

NSN 5910-00-932-2774

Glass Dielectric Variable Capacitor - Page 2 of 2



Shelf Li	fe:
----------	-----

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0