

View Online at <https://aerobasegroup.com/nsn/5910-00-934-2642>

Thread Class:

2a

Body Style:

Piston

Overall Length:

Between 0.485 inches and 0.547 inches

Terminal Length:

1.500 inches

Bushing Diameter:

Between 0.251 inches and 0.255 inches

Bushing Length:

0.063 mils and 0.125 centimeters

Body Length:

Between 0.282 inches and 0.344 inches

Overall Diameter:

0.266 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

75.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-75.0/+75.0 single section

Terminal Diameter:

0.016 inches

Quality Factor At 25 Deg Celsius:

1000.0

Fragility Factor:

Moderately rugged

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Bushing Width:

Between 0.230 inches and 0.235 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Capacitance Range In Picofarads:

+1.2/+16.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.08 single section

Material:

Glass capacitive electrode

Test Data Document:

13499-922-3038-140 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 tab, solder lug and 1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0