NSN 5910-00-934-3193

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-934-3193

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.615 inches
Body Width:
0.210 inches
Body Height:
0.390 inches
Center To Center Distance Between Terminals Parallel To Length:
0.200 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Licotrical i dianization.
Polarized
Polarized
Polarized Capacitance Value Per Section:
Polarized Capacitance Value Per Section: 18.000 microfarads single section
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp:
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp:
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section:
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section:
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Polarized Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic
Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material:
Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum
Capacitance Value Per Section: 18.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 8.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:

Terminal Surface Treatment:

Solder

NSN 5910-00-934-3193

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0