NSN 5910-00-934-3199

Quartz Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-934-3199 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 1.781 inches **Terminal Length:** 1.500 inches **Bushing Diameter:** 0.250 inches **Bushing Length:** 0.281 inches **Body Length:** 1.500 inches **Overall Diameter:** 0.575 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -100.0/+100.0 single section **Quality Factor At 25 Deg Celsius:** 2000.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round w/flat **Insulation Dc Resistance At Max Operating Temp:** 1000.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 200.0 degrees celsius **Thread Size:** 0.250 inches

Capacitance Range In Picofarads:

+0.9/+5.0 single section

Nonderated Voltage Rating And Type:

3500.0 ac peak single section

NSN 5910-00-934-3199

Quartz Dielectric Variable Capacitor - Page 2 of 2



| Adjustment Device Drive Type And Quantity: |
|--|
| 1 slotted screw |
| Terminal Type And Quantity: |
| 1 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A096a0