Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-936-1358

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.125 inches

Body Length:

0.930 inches

Body Width:

0.312 inches

Body Height:

0.100 inches

Center To Center Distance Between Terminals Parallel To Length:

0.700 inches

Terminal Diameter:

0.020 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

10000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-190.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Case Material:

Plastic

Dissipation Factor At Reference Tempurature In Percent:

0.0200

Test Data Document:

95542-108-621-1031 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0