NSN 5910-00-936-1939



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-936-1939 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 2.500 inches **Body Diameter:** 0.937 inches **Body Length:** 1.250 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 250.000 microfarads single section **Nonderated Operating Temp:** Between -20.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section Case Material: Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 45.0000 Dc Leakage At Reference Temp: 1.000 milliamperes **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic**

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-936-1939

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0