

View Online at <https://aerobasegroup.com/nsn/5910-00-937-8339>

Body Style:

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established/not established

Width Across Flats:

0.187 inches 0.187 inches

Body Length:

0.500 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Insulation Resistance At Maximum Operating Temp:

500.0 megohms

Capacitance Value Per Section:

0.100 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

25000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.5000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 wire hook/loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0