NSN 5910-00-937-9722

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-937-9722

| view Online at https://aerobasegroup.com/hsh/3310-00-337-3722 |
|--|
| Body Style: |
| W/thd mtg hol (s)/stud(s), terminal(s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.562 inches |
| Body Length: |
| 2.000 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 1.438 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.375 inches |
| Schematic Diagram Designator: |
| One terminal common to each section |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.813 inches |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Mounting Facility Type And Quantity: |
| 2 threaded mounting holes |
| Section Quantity: |
| 2 |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 4000.0000 picofarads all sections |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Thread Size: |
| 0.112 inches |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc all sections |
| Tolerance Range Per Section: |
| -1.00/+1.00 percent 2nd section |
| Case Material: |
| Metal |
| Test Data Document: |
| 56232-336852 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 standard tube base

NSN 5910-00-937-9722

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0