

View Online at https://aerobasegroup.com/nsn/5910-00-938-4620

## **Body Style:**

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

# **Reliability Indicator:**

Not establishednot establishednot established

# **Body Diameter:**

0.270 inches

## **Body Length:**

1.115 inches

# **Terminal Height From Body:**

1.250 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

### **Capacitance Value Per Section:**

200.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-330.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

### **Case Material:**

Ceramic

Insulation Resistance At Reference Temp:

50000.0 megohms

### **Quality Factor At Reference Temp:**

1000.0000

### **Terminal Surface Treatment:**

Solder

### Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0