

View Online at <https://aerobasegroup.com/nsn/5910-00-941-0390>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Established

**Terminal Length:**

1.500 inches

**Body Length:**

Between 0.285 inches and 0.300 inches

**Body Width:**

Between 0.285 inches and 0.300 inches

**Body Height:**

Between 0.090 inches and 0.100 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.190 inches and 0.210 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Capacitance Value Per Section:**

2700.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Ceramic

**Insulation Resistance At Reference Temp:**

40000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

2.5000

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

94756-441-0762 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0