NSN 5910-00-942-6725



Electrolytic Fixed Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-00-942-6725

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:
1.250 inches

Body Diameter:
0.422 inches

Body Length:
2.969 inches

Terminal Diameter:
0.025 inches

Schematic Diagram Designator:

. 1

No common or grounded electrode (s)

Anode Type:

Etched foil

Impedance At Minimum Operating Tempurature In Ohms:

23.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

150.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

675.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-15.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Tempurature In Percent:

15.0000

Dc Leakage At Reference Temp:

75.000 microamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-942-6725

Electrolytic Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0