

View Online at https://aerobasegroup.com/nsn/5910-00-944-2103

### **Body Style:**

W/thd mtg studs, axial terminals

#### **Reliability Indicator:**

Not established

## **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.562 inches

#### **Body Length:**

1.125 inches

### **Terminal Diameter:**

#### 0.032 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.625 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Mounting Facility Screw Thread Series Designator:

Unc

### Mounting Facility Type And Quantity:

2 threaded mounting studs

# **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

### Capacitance Value Per Section:

1.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Thread Size:

0.138 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

### Power Factor At Reference Tempurature In Percent:

1.0000

### **Terminal Surface Treatment:**

Solder



Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0