

View Online at https://aerobasegroup.com/nsn/5910-00-944-4421

## **Body Style:**

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

### **Reliability Indicator:**

Not establishednot establishednot established

## **Terminal Length:**

1.250 inches 1.250 inches

#### **Body Diameter:**

0.200 inches

#### **Body Length:**

0.400 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.250 inches

**Terminal Diameter:** 

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

1.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-2200.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-400.0/+400.0 single section

### **Tolerance Range Per Section:**

-0.25/+0.25 picofarads single section

### Case Material:

Plastic

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.5000

# **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 uninsulated wire lead

### Shelf Life:

N/a

### Unit Of Measure:

---

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0