NSN 5910-00-944-9322

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-944-9322 **Body Style:** Piston **Overall Length:** 1.211 inches **Body Length:** 1.000 inches **Overall Diameter:** 0.250 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -100.0/+100.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Center To Center Distance Between Terminals Parallel To Diameter:** Between 0.234 inches and 0.281 inches **Quality Factor At 25 Deg Celsius:** 700.0 **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Insulation Dc Resistance At Max Operating Temp:** 100000.0 megohms **Mounting Facility Type And Quantity:** 4 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +0.8/+18.0 single section **Nonderated Voltage Rating And Type:** 750.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Capacitance Drift In Picofarads: 0.04 single section **Terminal Type And Quantity:** 4 wire lead Shelf Life: N/a **Unit Of Measure:**

--

NSN 5910-00-944-9322

Glass Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0