

View Online at https://aerobasegroup.com/nsn/5910-00-946-5671

Body Style:

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surface

Reliability Indicator: Not establishednot establishednot established **Terminal Length:** 1.250 inches 1.250 inches **Body Length:** Between 0.180 inches and 0.200 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.080 inches and 0.100 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.085 inches and 0.115 inches **Terminal Diameter:** Between 0.023 inches and 0.029 inches Schematic Diagram Designator: No common or grounded electrode (s) Insulation Resistance At Maximum Operating Temp: 10000.0 megohms **Capacitance Value Per Section:** 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -60.0/+60.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.150 **Terminal Surface Treatment:**

Solder

Terminal Type And Quantity:

2 uninsulated wire lead



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0